



WEBLOG 250 / WEBLOG 120

NEW

- M-Bus data logger for 250 or 120 meters
- 7" LED Touchscreen
- Remote readout via web browser
- USB, Ethernet, W-LAN, RS232C, Modem (analogue/GPRS)
- Data export as XML, XLSX, CSV via E-Mail, FTP, USB

The new generation

The new web connectable central unit with touch screen and 1GB memory fits as flexible to your needs as no Relay data logger did before. We offer the device in two versions:

WebLog 250 for up to 250 meters and WebLog 120 for up to 120 meters. The total number can be extended up to 1000 meters by using M-Bus repeaters. In addition to the standard interfaces (USB, RS-232C, Ethernet) the customer can choose between optional WiFi, analogue or GSM modem. →



Remote access via web browser

WebLog M-Bus center

up to 250 meters

Operation and Features

The WebLog is operated by the 7" wide LED touch screen or with your PC / Laptop via the web browser. The logged data can be exported to an USB flash drive, FTP server or via email to csv, xls or xml files. 2 inputs for potential-free contact (status indicator) and 3 relay outputs complete the functionality of the WebLog centers. By the built in universal Power Supply (110-250 V AC) and the robust ABS plastic housing with separate terminal compartment, it adapts also perfectly to the requirements of the installation practice. Mounting can be done either on a DIN rail or on the wall. By an optional cylinder lock, the device can be secured from unauthorized access. In order to complete the functionality of the WebLog, the software allows a structured user management with different access rights and the management of multiple counter groups and different reading intervals. In addition, you can always choose between the implemented languages for the user interface. Installation and configuration of the WebLog central units are made much more easier by a built in wizard, that guides you step by step to the finished installation.

Specifications

Operating voltage	110 .. 250VAC, 47 .. 63 Hz
Power consumption	max. 100W
Temperature range	0 .. 55°C
M-Bus voltage	42 V (Mark ohne Last)
M-Bus Standby current	max. 375 mA
Overcurrent threshold	500mA
Bus impedance	8 Ω
M-Bus baud rate	300 .. 9600 Baud
Galvanic isolation	available
Housing	light grey ABS plastic, protection class IP 52 H x B x T: 264 x 234 x 86 mm mounting on DIN rail or wall, optional cylinder lock
LED status indicators	power, communication, maximum load M-Bus, M-Bus short circuit
Display	7" LED display with resistive touch screen 800 x 480 pixels 262144 colors
Memory	1 GB Flash memory
Interfaces	10/100 MBit Ethernet, USB-Host, USB-Device, RS232 optional: W-LAN, analogue modem or GPRS modem
Terminals	3 x terminals for M-Bus, plug-in terminals for floating contacts and relay outputs

Ordering

Article number	Description
WEBLOG250	web enabled M-Bus center for up to 250 meters
WEBLOG120	web enabled M-Bus center for up to 120 meters

Accessories

Article number	Description
KA003	2m power cord, safety plug
IMOD001	analog modem, internal
IMOD002	GPRS modem, internal